

FORTE Slewing Bearings






FORTE machinery – a specialized slewing bearing designing and manufacturing company in association with its strategic manufacturers in China.

FORTE slewing bearing covers ball type, roller type, ball and roller combination type, without gear, with external gear, with internal gear slewing rings in following structures, Single-row four-point contact ball bearing slewing rings, Double-row angular contact thrust ball bearing slewing rings, Cross cylindrical roller bearing slewing rings, Cross taper roller bearing slewing rings, Triple-row roller combination bearing slewing rings, widely used in the application of robotic automations, general mechanical engineering, vehicle construction, stacker and reclaimer, mechanical handling, mining and materials handling systems, harbor tower cranes, ship crane equipment and off-shore technology. Nowadays, FORTE is successfully accessed with Blade, Yaw and Single Main Bearings in the projects of Wind Turbines ranging from 10 KW to 3.5 MW and Tunnel Machine Bearings in the projects of Tunnel Engineering Construction.

FORTE slewing bearing size range is from 200 mm I.D. to 16,000 mm O.D. in monobloc system and segmental system in large dimensions. For the robot slewing rings ranging below 850 mm O.D., gear tooth tolerance is available to achieve Grade DIN 5.






SINGLE-ROW FOUR-POINT CONTACT BALL BEARING SLEWING RINGS






轴承型号Designations			外形尺寸 Boundary dimensions			安 装 孔 尺 寸 Bolt hole diameter			结 构 尺 寸 Structure dimensions						齿 轮 参 数 Gear parameters						额定负荷 Basic load ratings	质量 Mass		
无齿式	外齿式	内齿式	D	d	H	D1	D2	n	φ	D3	d1	H1	h	n3	φ3	m	Da	Z	da	Z	b	x	Coa	kg
non-gear type	external gear type	internal gear type	mm			mm		n	mm	mm					n3	mm		mm		mm		mm	10 ⁴ N	
010-30-500-** 010-30-560-** 010-30-630-** 010-30-710-** <																								

SINGLE-ROW FOUR-POINT CONTACT BALL BEARING SLEWING RINGS






轴承型号Designations			外形尺寸 Boundary dimensions			安 装 孔 尺 寸 Bolt hole diameter				结 构 尺 寸 Structure dimensions						齿 轮 参 数 Gear parameters							额定负荷 Basic load ratings	质量 Mass
无齿式	外齿式	内齿式	D	d	H	D1	D2	n	φ	D3	d1	H1	h	n3	φ3	m	Da	Z	da	Z	b	x	Coa	kg
non-gear type	external gear type	internal gear type	mm			mm			mm	mm					mm		mm		mm		mm		mm	
010-60-2240-** 010-60-2500-** 010-60-2500-** 010-60-2800-**	011-60-2240-**	013-60-2240-**	2418	2065	144	2350	2131	48	33	2237.5	2242.5	132	12	8	M10×1	16	2496	153	1984	125	120	+0.5	1350	1250
	012-60-2240-**	014-60-2240-**	2418	2065	144	2350	2131	48	33	2237.5	2242.5	132	12	8	M10×1	18	2502	136	1980	111	120	+0.5	1350	1250
	011-60-2500-**	013-60-2500-**	2678	2325	144	2610	2391	56	33	2497.5	2502.5	132	12	8	M10×1	18	2772	151	2232	125	120	+0.5	1500	1400
	012-60-2500-**	014-60-2500-**	2678	2325	144	2610	2391	56	33	2497.5	2502.5	132	12	8	M10×1	20	2780	136	2220	112	120	+0.5	1500	1400
	011-40-2500-12		2678	2325	144	2610	2391	56	33	2498	2502	132	12	8	M10×1	18	2769.7	151	--	--	120	+0.5	820	890
010-60-2800-**	011-60-2800-**	013-60-2800-**	2978	2625	144	2910	2691	56	33	2797.5	2802.5	132	12	8	M10×1	18	3078	168	2520	141	120	+0.5	1680	1600
	012-60-2800-**	014-60-2800-**	2978	2625	144	2910	2691	56	33	2797.5	2802.5	132	12	8	M10×1	20	3080	151	2520	127	120	+0.5	1680	1600
010-75-3150-**	011-75-3150-**	013-75-3150-**	3376	2922	174	3286	3014	56	45	3147.5	3152.5	162	12	8	M10×1	20	3480	171	2820	142	150	+0.5	2380	2800
	012-75-3150-**	014-75-3150-**	3376	2922	174	3286	3014	56	45	3147.5	3152.5	162	12	8	M10×1	22	3476	115	2816	129	150	+0.5	2380	2800
010-75-3550-**	011-75-3550-**	013-75-3550-**	3776	3322	174	3686	3414	56	45	3547.5	3552.5	162	12	8	M10×1	20	3880	191	3220	162	150	+0.5	2690	3200
	012-75-3550-**	014-75-3550-**	3776	3322	174	3686	3414	56	45	3547.5	3552.5	162	12	8	M10×1	22	3894	174	3212	147	150	+0.5	2690	3200
010-75-4000-**	011-75-4000-**	013-75-4000-**	4226	3772	174	4136	3864	60	45	3997.5	4002.5	162	12	10	M10×1	22	4334	194	3652	167	150	+0.5	3020	3600
	012-75-4000-**	014-75-4000-**	4226	3772	174	4136	3864	60	45	3997.5	4002.5	162	12	10	M10×1	25	4350	171	3650	147	150	+0.5	3020	3600
010-75-4500-**	011-75-4500-**	013-75-4500-**	4726	4272	174	4636	4364	60	45	4497.5	4502.5	162	12	10	M10×1	22	4840	271	4158	190	150	+0.5	3410	4000
	012-75-4500-**	014-75-4500-**	4726	4272	174	4636	4364	60	45	4497.5	4502.5	162	12	10	M10×1	25	4850	191	4150	167	150	+0.5	3410	4000

DOUBLE-ROW ANGULAR CONTACT TRUST BALL BEARING SLEWING RINGS






轴承型号Designations			外形尺寸 Boundary dimensions			安装孔尺寸 Bolt hole diameter			结构尺寸 Structure dimensions							齿轮参数 Gear parameters							额定负荷 Basic load ratings	质量 Mass
无齿式 non-gear type	外齿式 external gear type	内齿式 internal gear type	D	d	H	D1	D2	n	φ	D3	d1	H1	h	n3	φ3	m	Da	Z	da	Z	b	x	Coa	kg
			mm			mm			mm	(D3')	(d1')				mm		mm		mm		mm		10 ⁴ N	
020-25-500-**-	021-25-500-**-	023-25-500-**-	616	384	106	580	420	20	18	523	517	96	26	4	M10×1	5	645	126	355	72	60	+0.5	121	100
	022-25-500-**-	024-25-500-**-	616	384	106	580	420	20	18	(483)	(477)	96	26	4	M10×1	6	648	105	348	59	60	+0.5	121	100
020-25-560-**-	021-25-560-**-	023-25-560-**-	676	444	106	640	480	20	18	583	577	96	26	4	M10×1	5	705	138	415	84	60	+0.5	134	115
	022-25-560-**-	024-25-560-**-	676	444	106	640	480	20	18	(543)	(537)	96	26	4	M10×1	6	708	115	408	69	60	+0.5	134	115
020-25-630-**-	021-25-630-**-	023-25-630-**-	746	514	106	710	550	24	18	653	647	96	26	4	M10×1	6	792	129	480	81	60	+0.5	153	130
	022-25-630-**-	024-25-630-**-	746	514	106	710	550	24	18	(613)	(607)	96	26	4	M10×1	8	792	96	472	60	60	+0.5	153	130
020-25-710-**-	021-25-710-**-	023-25-710-**-	826	594	106	790	630	24	18	733	727	96	26	4	M10×1	6	864	141	558	94	60	+0.5	173	140
	022-25-710-**-	024-25-710-**-	826	594	106	790	630	24	18	(693)	(687)	96	26	4	M10×1	8	864	105	552	70	60	+0.5	173	140
020-30-800-**-	021-30-800-**-	023-30-800-**-	942	658	124	898	702	30	22	828	822	114	29	6	M10×1	8	984	120	616	78	80	+0.5	230	200
	022-30-800-**-	024-30-800-**-	942	658	124	898	702	30	22	(778)	(771)	114	29	6	M10×1	10	990	96	610	62	80	+0.5	230	200
020-30-900-**-	021-30-900-**-	023-30-900-**-	1042	758	124	998	802	30	22	928	922	114	29	6	M10×1	8	1088	133	712	90	80	+0.5	258	250
	022-30-900-**-	024-30-900-**-	1042	758	124	998	802	30	22	(878)	(871)	114	29	6	M10×1	10	1090	106	710	72	80	+0.5	258	250
020-30-1000-**-	021-30-1000-**-	023-30-1000-**-	1142	858	124	1098	902	36	22	1028	1022	114	29	6	M10×1	10	1200	117	810	82	80	+0.5	286	300
	022-30-1000-**-	024-30-1000-**-	1142	858	124	1098	902	36	22	(978)	(971)	114	29	6	M10×1	12	1200	97	792	67	80	+0.5	286	300
020-30-1120-**-	021-30-1120-**-	023-30-1120-**-	1262	978	124	1218	1022	36	22	1148	1142	114	29	6	M10×1	10	1320	129	920	93	80	+0.5	321	340
	022-30-1120-**-	024-30-1120-**-	1262	978	124	1218	1022	36	22	(1098)	(1091)	114	29	6	M10×1	12	1320	107	912	77	80	+0.5	321	340
020-40-1250-**-	021-40-1250-**-	023-40-1250-**-	1426	1074	160	1374	1126	40	26	1286	1282	150	39	6	M10×1	12	1500	122	1008	85	90	+0.5	482	580
	022-40-1250-**-	024-40-1250-**-	1426	1074	160	1374	1126	40	26	(1218)	(1214)	150	39	6	M10×1	14	1498	104	1008	73	90	+0.5	482	580
020-40-1400-**-	021-40-1400-**-	023-40-1400-**-	1576	1224	160	1524	1272	40	26	1436	1432	150	39	6	M10×1	12	1644	134	1152	97	90	+0.5	543	650
	022-40-1400-**-	024-40-1400-**-	1576	1224	160	1524	1272	40	26	(1368)	(1364)	150	39	6	M10×1	14	1652	115	1148	83	90	+0.5	543	650
020-40-1600-**-	021-40-1600-**-	023-40-1600-**-	1776	1424	160	1724	1476	45	26	1636	1632	150	39	8	M10×1	14	1848	129	1344	97	90	+0.5	620	750
	022-40-1600-**-	024-40-1600-**-	1776	1424	160	1724	1476	45	26	(1568)	(1564)	150	39	8	M10×1	16	1856	113	1344	85	90	+0.5	620	750
020-40-1800-**-	021-40-1800-**-	023-40-1800-**-	1976	1624	160	1924	1676	45	26	1836	1832	150	39	8	M10×1	14	2058	144	1540	111	90	+0.5	692	820
	022-40-1800-**-	024-40-1800-**-	1976	1624	160	1924	1676	45	26	(1768)	(1764)	150	39	8	M10×1	16	2064	126	1536	97	90	+0.5	692	820
020-50-2000-**-	021-50-2000-**-	023-50-2000-**-	2215	1785	190	2149	1851	48	33	2038	2032	178	47	8	M10×1	16	2304	141	1696	107	120	+0.5	987	1150
	022-50-2000-**-	024-50-2000-**-	2215	1785	190	2149	1851	48	33	(1968)	(1962)	178	47	8	M10×1	18	2304	125	1692	95	120	+0.5	987	1150
020-50-2240-**-	021-50-2240-**-	023-50-2240-**-	2455	2025	190	2389	2091	48	33	2278	2272	178	47	8	M10×1	16	2544	156	1936	122	120	+0.5	1110	1500
	022-50-2240-**-	024-50-2240-**-	2455	2025	190	2389	2091	48	33	(2208)	(2202)	178	47	8	M10×1	18	2556	139	1926	108	120	+0.5	1110	1500

DOUBLE-ROW ANGULAR CONTACT TRUST BALL BEARING SLEWING RINGS






轴承型号Designations			外形尺寸 Boundary dimensions			安 装 孔 尺 寸 Bolt hole diameter		结 构 尺 寸 Structure dimensions							齿 轮 参 数 Gear parameters						额定负荷 Basic load ratings	质量 Mass		
无齿式	外齿式	内齿式	D	d	H	D1	D2	n	φ	D3	d1	H1	h	n3	φ3	m	Da	Z	da	Z	b	x	Coa	kg
non-gear type	external gear type	internal gear type	mm			mm			mm	(D3')	(d1')				mm		mm		mm		mm		10 ⁴ N	
020-50-2500.**	021-50-2500.**	023-50-2500.**	2715	2285	190	2649	2351	56	33	2538	2532	78	47	8	M10×1	18	2804	153	2196	123	120	+0.5	1110	1500
	022-50-2500.**	024-50-2500.**	2715	2285	190	2649	2351	56	33	(2468)	(2462)	78	47	8	M10×1	20	2820	138	2180	110	120	+0.5	1110	1500
	021-50-2500-12		2715	2285	190	2649	2351	56	33	2550	2538	178	47	8	M10×1	18	2804.4	153		120	+0.5	1117	2031	
020-50-2800.**	021-50-2800.**	023-50-2800.**	3015	2585	190	2949	2651	56	33	2838	2832	178	47	8	M10×1	18	3114	170	2484	139	120	+0.5	1390	1900
	022-50-2800.**	024-50-2800.**	3015	2585	190	2949	2651	56	33	(2768)	(2762)	178	47	8	M10×1	20	3120	153	2480	125	120	+0.5	1390	1900
020-60-3150.**	021-60-3150.**	023-60-3150.**	3428	2872	226	3338	2962	56	45	3198	3192	214	56	8	M10×1	20	3540	174	2760	139	150	+0.5	1870	3300
	022-60-3150.**	024-60-3150.**	3428	2872	226	3338	2962	56	45	(3108)	(3102)	214	56	8	M10×1	22	3542	158	2750	126	150	+0.5	1870	3300
020-60-3550.**	021-60-3550.**	023-60-3550.**	3828	3272	226	3738	3362	56	45	3598	3592	214	56	8	M10×1	20	3940	194	3160	159	150	+0.5	2110	3700
	022-60-3550.**	024-60-3550.**	3828	3272	226	3738	3362	56	45	(3508)	(3502)	214	56	8	M10×1	22	3938	176	3168	145	150	+0.5	2110	3700
020-60-4000.**	021-60-4000.**	023-60-4000.**	4278	3722	226	4188	3812	60	45	4048	4042	214	56	10	M10×1	22	4400	197	3608	165	150	+0.5	2370	4200
	022-60-4000.**	024-60-4000.**	4278	3722	226	4188	3812	60	45	(3958)	(3952)	214	56	10	M10×1	25	4400	173	3600	145	150	+0.5	2370	4200
020-60-4500.**	021-60-4500.**	023-60-4500.**	4778	4222	226	4688	4312	60	45	4548	4542	214	56	10	M10×1	22	4884	219	4114	188	150	+0.5	2670	4700
	022-60-4500.**	024-60-4500.**	4778	4222	226	4688	4312	60	45	(4458)	(4452)	214	56	10	M10×1	25	4900	193	4100	165	150	+0.5	2670	4700

CROSS CYLINDRICAL ROLLER BEARING SLEWING RINGS






轴承型号Designations			外形尺寸 Boundary dimensions			安 装 孔 尺 寸 Bolt hole diameter				结 构 尺 寸 Structure dimensions						齿 轮 参 数 Gear parameters						额定负荷 Basic load ratings	质量 Mass	
无齿式	外齿式	内齿式	D	d	H	D1	D2	n	φ	D3	d1	H1	h	n3	φ3	m	Da	Z	da	Z	b	x	Coa	kg
non-gear type	external gear type	internal gear type	mm			mm			mm	mm					mm		mm	mm	mm	mm	mm		mm	
110-25-500.**	111-25-500.**	113-25-500.**	602	398	75	566	434	20	18	499	501	65	10	4	M10×1	5	630	123	365	74	60	0.5	104	80
	112-25-500.**	114-25-500.**	602	398	75	566	434	20	18	499	501	65	10	4	M10×1	6	630	120	360	62	60	0.5	104	80
110-25-560.**	111-25-560.**	113-25-560.**	662	458	75	626	494	20	18	558.5	561.5	65	10	4	M10×1	5	690	135	425	86	60	0.5	116	90
	112-25-560.**	114-25-560.**	662	458	75	626	494	20	18	558.5	561.5	65	10	4	M10×1	6	690	112	426	112	60	0.5	116	90
110-25-630.**	111-25-630.**	113-25-630.**	732	528	75	696	564	24	18	628.5	631.5	65	10	4	M10×1	6	774	126	492	83	60	0.5	130	100
	112-25-630.**	114-25-630.**	732	528	75	696	564	24	18	628.5	631.5	65	10	4	M10×1	8	776	94	488	62	60	0.5	130	100
110-25-710.**	111-25-710.**	113-25-710.**	812	608	75	776	644	24	18	708.5	711.5	65	10	4	M10×1	6	852	139	570	96	60	0.5	149	110
	112-25-710.**	114-25-710.**	812	608	75	776	644	24	18	708.5	711.5	65	10	4	M10×1	8	856	104	568	72	60	0.5	149	110
110-28-800.**	111-28-800.**	113-28-800.**	922	678	82	878	722	30	22	798.5	801.5	72	10	6	M10×1	8	968	118	632	80	65	0.5	185	170
	112-28-800.**	114-28-800.**	922	678	82	878	722	30	22	798.5	801.5	72	10	6	M10×1	10	970	94	630	64	65	0.5	185	170
110-28-900.**	111-28-900.**	113-28-900.**	1022	778	82	978	822	30	22	898.5	901.5	72	10	6	M10×1	8	1064	130	736	93	65	0.5	209	190
	112-28-900.**	114-28-900.**	1022	778	82	978	822	30	22	898.5	901.5	72	10	6	M10×1	10	1070	104	730	74	65	0.5	209	190
110-28-1000.**	111-28-1000.**	113-28-1000.**	1122	878	82	1078	922	36	22	998.5	1001.5	72	10	6	M10×1	10	1190	116	820	83	65	0.5	233	210
	112-28-1000.**	114-28-1000.**	1122	878	82	1078	922	36	22	998.5	1001.5	72	10	6	M10×1	12	1188	96	816	69	65	0.5	233	210
110-28-1120.**	111-28-1120.**	113-28-1120.**	1242	998	82	1198	1042	36	22	1118	1122	72	10	6	M10×1	10	1300	127	940	95	65	0.5	262	230
	112-28-1120.**	114-28-1120.**	1242	998	82	1198	1042	36	22	1118	1122	72	10	6	M10×1	12	1308	106	936	79	65	0.5	262	230
110-32-1250.**	111-32-1250.**	113-32-1250.**	1390	1110	91	1337	1163	40	26	1248	1252	81	10	6	M10×1	12	1452	118	1044	88	75	0.5	321	350
	112-32-1250.**	114-32-1250.**	1390	1110	91	1337	1163	40	26	1248	1252	81	10	6	M10×1	14	1456	101	1036	75	75	0.5	321	350
110-32-1400.**	111-32-1400.**	113-32-1400.**	1540	1260	91	1487	1313	40	26	1398	1402	81	10	6	M10×1	12	1608	131	1188	100	75	0.5	358	400
	112-32-1400.**	114-32-1400.**	1540	1260	91	1487	1313	40	26	1398	1402	81	10	6	M10×1	14	1610	112	1190	86	75	0.5	358	400
110-32-1600.**	111-32-1600.**	113-32-1600.**	1740	1460	91	1687	1513	45	26	1598	1602	81	10	8	M10×1	14	1820	127	1386	100	75	0.5	412	440
	112-32-1600.**	114-32-1600.**	1740	1460	91	1687	1513	45	26	1598	1602	81	10	8	M10×1	16	1824	111	1376	87	75	0.5	412	440
110-32-1800.**	111-32-1800.**	113-32-1800.**	1940	1660	91	1887	1713	45	26	1798	1802	81	10	8	M10×1	14	2016	141	1568	113	75	0.5	460	500
	112-32-1800.**	114-32-1800.**	1940	1660	91	1887	1713	45	26	1798	1802	81	10	8	M10×1	16	2016	123	1568	99	75	0.5	460	500
		113-45-1830-11	2002	1665	156	1940	1720	54	30	1827	1833	128	28	6	M10×1	12	--	--	1610	135	100	0.5	571	912

CROSS CYLINDRICAL ROLLER BEARING SLEWING RINGS






轴承型号Designations			外形尺寸 Boundary dimensions			安 装 孔 尺寸 Bolt hole diameter				结 构 尺寸 Structure dimensions						齿 轮 参 数 Gear parameters						额定负荷 Basic load ratings	质量 Mass	
无齿式	外齿式	内齿式	D	d	H	D1	D2	n	φ	D3	d1	H1	h	n3	φ3	m	Da	Z	da	Z	b	x	Coa	kg
non-gear type	external gear type	internal gear type	mm			mm			mm	mm					mm		mm		mm		mm		10 ⁴ N	
110-40-2000-**	111-40-2000-**	113-40-2000-**	2178	1825	112	2110	1891	48	33	1998	2002	100	12	8	M10×1	16	2272	139	1728	109	90	0.5	686	900
	112-40-2000-**	114-40-2000-**	2178	1825	112	2110	1891	48	33	1998	2002	100	12	8	M10×1	18	2268	123	1728	97	90	0.5	686	900
110-40-2000-12			2178	1825	112	2110	1891	48	33	1991	1995	100	12	8	M10×1	--	--	--	--	--	--	--	635	767
110-40-2240-**	111-40-2240-**	113-40-2240-**	2418	2065	112	2350	2131	48	33	2237.5	2242.5	100	12	8	M10×1	16	2496	153	1984	125	90	0.5	764	1000
	112-40-2240-**	114-40-2240-**	2418	2065	112	2350	2131	48	33	2237.5	2242.5	100	12	8	M10×1	18	2502	136	1980	111	90	0.5	764	1000
110-40-2500-**	111-40-2500-**	113-40-2500-**	2678	2325	112	2610	2391	56	33	2497.5	2502.5	100	12	8	M10×1	18	2772	151	2232	125	90	0.5	797	876
	112-40-2500-**	114-40-2500-**	2678	2325	112	2610	2391	56	33	2497.5	2502.5	100	12	8	M10×1	20	2780	136	2220	112	90	0.5	797	876
	112-40-2500-12K		2678	2325	112	2610	2391	56	33	2498.5	2501.5	100	112	8	M16×1.5	--	--	--	--	--	--	--	1000	876
110-40-2800-**	111-40-2800-**	113-40-2800-**	2978	2625	112	2910	2691	56	33	2797.5	2802.5	100	12	8	M10×1	18	3078	168	2520	141	90	0.5	960	1250
	112-40-2800-**	114-40-2800-**	2978	2625	112	2910	2691	56	33	2797.5	2802.5	100	12	8	M10×1	20	3080	151	2520	127	90	0.5	960	1250
110-50-3150-**	111-50-3150-**	113-50-3150-**	3376	2922	134	3286	3014	56	45	3147.5	3152.5	122	12	8	M10×1	20	3480	171	2820	142	110	0.5	1380	2150
	112-50-3150-**	114-50-3150-**	3376	2922	134	3286	3014	56	45	3147.5	3152.5	122	12	8	M10×1	22	3476	155	2816	129	110	0.5	1380	2150
110-50-3550-**	111-50-3550-**	113-50-3550-**	3776	3322	134	3686	3414	56	45	3547.5	3552.5	122	12	8	M10×1	20	3880	191	3220	162	110	0.5	1570	2470
	112-50-3550-**	114-50-3550-**	3776	3322	134	3686	3414	56	45	3547.5	3552.5	122	12	8	M10×1	22	3894	174	3212	147	110	0.5	1570	2470
	111-52-3550-12		3776	3322	134	3686	3414	56	45	3548	3552	122	12	8	M10×1	20	3880	191	--	--	110	0.5	1475	2464
110-50-4000-**	111-50-4000-**	113-50-4000-**	4226	3772	134	4136	3864	60	45	3997.5	4002.5	122	12	10	M10×1	22	4334	194	3652	167	110	0.5	1760	2800
	112-50-4000-**	114-50-4000-**	4226	3772	134	4136	3864	60	45	3997.5	4002.5	122	12	10	M10×1	25	4350	171	3650	147	110	0.5	1760	2800
110-50-4500-**	111-50-4500-**	113-50-4500-**	4726	4272	134	4636	4364	60	45	4497.5	4502.5	122	12	10	M10×1	22	4940	217	4158	190	110	0.5	1980	3100
	112-50-4500-**	114-50-4500-**	4726	4272	134	4636	4364	60	45	4497.5	4502.5	122	12	10	M10×1	25	4850	191	4150	167	110	0.5	1980	3100

CROSS TAPER ROLLER BEARING SLEWING RINGS






轴承型号Designations			外形尺寸 Boundary dimensions			安 装 孔 尺 寸 Bolt hole diameter			结 构 尺 寸 Structure dimensions						齿 轮 参 数 Gear parameters						额定负荷 Basic load ratings	质量 Mass			
无齿式	外齿式	内齿式	D	d	H	D1	D2	n	φ	D3	d1	H1	h	n3	φ3	m	Da	Z	da	Z	b	x	Coa	kg	
non-gear type	external gear type	internal gear type	mm			mm			mm	mm					mm		mm		mm		mm	mm	10 ⁴ N		
5792/900			1150	900	90	1105	950	24	19	1021	1025	78	12	6	M8×1	--	--	--	--	--	--	--	--	165	227
		3-935G	940	--	90	900	752	24	19 17	823	827	78	12	6	M8×1	4	--	--	672	170	78	0	133	180	
		7797/1660G	2150	1660	245	2100	1735	30	32	1909	1921	220	25	3	M10×1	16	--	--	1581.1	100	190	+0.35	996	2194	
120-25-500-**-	121-25-500-**-	123-25-500-**-	602	398	75	566	434	20	18	498.5	501.5	65	10	4	M10×1	5	630	123	365	74	60	+0.5	104	80	
	122-25-500-**-	124-25-500-**-	602	398	75	566	434	20	18	498.5	501.5	65	10	4	M10×1	6	630	102	366	62	60	+0.5	104	80	
120-25-560-**-	121-25-560-**-	123-25-560-**-	662	458	75	626	494	20	18	558.5	561.5	65	10	4	M10×1	5	690	135	425	86	60	+0.5	116	90	
	122-25-560-**-	124-25-560-**-	662	458	75	626	494	20	18	558.5	561.5	65	10	4	M10×1	6	690	112	426	72	60	+0.5	116	90	
120-25-630-**-	121-25-630-**-	123-25-630-**-	732	528	75	696	564	24	18	628.5	631.5	65	10	4	M10×1	6	774	126	492	83	60	+0.5	130	100	
	122-25-630-**-	124-25-630-**-	732	528	75	696	564	24	18	628.5	631.5	65	10	4	M10×1	8	776	94	488	62	60	+0.5	130	100	
120-25-710-**-	121-25-710-**-	123-25-710-**-	812	608	75	776	644	24	18	708.5	712.5	65	10	4	M10×1	6	852	139	570	96	60	+0.5	149	110	
	122-25-710-**-	124-25-710-**-	812	608	75	776	644	24	18	708.5	712.5	65	10	4	M10×1	8	856	104	568	72	60	+0.5	149	110	
120-28-800-**-	121-28-800-**-	123-28-800-**-	922	678	82	878	722	30	22	798.5	801.5	72	10	6	M10×1	8	968	118	632	80	65	+0.5	185	170	
	122-28-800-**-	124-28-800-**-	922	678	82	878	722	30	22	798.5	801.5	72	10	6	M10×1	10	970	94	630	64	65	+0.5	185	170	
120-28-900-**-	121-28-900-**-	123-28-900-**-	1022	778	82	978	822	30	22	898.5	901.5	72	10	6	M10×1	8	1064	130	736	93	65	+0.5	209	190	
	122-28-900-**-	124-28-900-**-	1022	778	82	978	822	30	22	898.5	901.5	72	10	6	M10×1	10	1070	104	730	74	65	+0.5	209	190	
120-28-1000-**-	121-28-1000-**-	123-28-1000-**-	1122	878	82	1078	922	36	22	998.5	1001.5	72	10	6	M10×1	10	1190	116	820	83	65	+0.5	233	210	
	122-28-1000-**-	124-28-1000-**-	1122	878	82	1078	922	36	22	998.5	1001.5	72	10	6	M10×1	12	1188	96	816	69	65	+0.5	233	210	
120-28-1120-**-	121-28-1120-**-	123-28-1120-**-	1242	998	82	1198	1042	36	22	1118	1122	72	10	6	M10×1	10	1300	127	940	95	65	+0.5	262	230	
	122-28-1122-**-	124-28-1120-**-	1242	998	82	1198	1042	36	22	1118	1122	72	10	6	M10×1	12	1308	106	936	79	65	+0.5	262	230	
120-32-1250-**-	121-32-1250-**-	123-32-1250-**-	1390	1110	91	1337	1163	40	26	1248	1252	81	10	6	M10×1	12	1452	118	1044	88	75	+0.5	321	350	
	122-32-1250-**-	124-32-1250-**-	1390	1110	91	1337	1163	40	26	1248	1252	81	10	6	M10×1	14	1456	101	1036	75	75	+0.5	321	350	
120-32-1400-**-	121-32-1400-**-	123-32-1400-**-	1540	1260	91	1487	1313	40	26	1398	1402	81	10	6	M10×1	12	1608	131	1188	100	75	+0.5	358	400	
	122-32-1400-**-	124-32-1400-**-	1540	1260	91	1487	1313	40	26	1398	1402	81	10	6	M10×1	14	1610	112	1190	86	75	+0.5	358	400	

CROSS TAPER ROLLER BEARING SLEWING RINGS






轴承型号Designations			外形尺寸 Boundary dimensions			安 装 孔 尺 寸 Bolt hole diameter				结 构 尺 寸 Structure dimensions						齿 轮 参 数 Gear parameters						额定负荷 Basic load ratings	质量 Mass	
无齿式	外齿式	内齿式	D	d	H	D1	D2	n	φ	D3	d1	H1	h	n3	φ3	m	Da	Z	da	Z	b	x	Coa	kg
non-gear type	external gear type	internal gear type	mm			mm			mm	mm					mm		mm		mm		mm	mm	10 ⁴ N	
120-32-1600-03K	121-32-1600-03K	123-32-1600-03K	1740	1460	91	1687	1513	45	26	1598	1602	81	10	8	M10×1	14	1820	127	1386	100	75	+0.5	412	440
	122-32-1600-03K	124-32-1600-03K	1740	1460	91	1687	1513	45	26	1598	1602	81	10	8	M10×1	16	1824	111	1376	87	75	+0.5	412	440
	121-32-1600-03K	123-32-1600-03K	1740	1460	100	1687	1513	48	26	1598	1602	90	10	8	M10×1	--	--	--	--	--	--	--	469	429
	121-32-1800-03K	123-32-1800-03K	1940	1660	91	1887	1713	45	26	1798	1802	81	10	8	M10×1	14	2016	141	1568	113	75	+0.5	460	500
	122-32-1800-03K	124-32-1800-03K	1940	1660	91	1887	1713	45	26	1798	1802	81	10	8	M10×1	16	2016	123	1568	99	75	+0.5	460	500
120-40-2000-03K	121-40-2000-03K	123-40-2000-03K	2178	1825	112	2110	1891	48	33	1998	2002	100	12	8	M10×1	16	2272	139	1728	109	90	+0.5	686	900
	122-40-2200-03K	124-40-2000-03K	2178	1825	112	2110	1891	48	33	1998	2002	100	12	8	M10×1	18	2268	123	1728	97	90	+0.5	686	900
	121-40-2240-03K	123-40-2240-03K	2418	2065	112	2350	2131	48	33	2237.5	2242.5	100	12	8	M10×1	16	2496	153	1984	125	90	+0.5	764	1000
	122-40-2240-03K	124-40-2240-03K	2418	2065	112	2350	2131	48	33	2237.5	2242.5	100	12	8	M10×1	18	2502	136	1980	111	90	+0.5	764	1000
	121-40-2500-03K	123-40-2500-03K	2678	2325	112	2610	2391	56	33	2497.5	2502.5	100	12	8	M10×1	18	2772	151	2232	125	90	+0.5	852	1100
120-40-2500-03K	122-40-2500-03K	124-40-2500-03K	2678	2325	112	2610	2391	56	33	2497.5	2502.5	100	12	8	M10×1	20	2780	136	2220	112	90	+0.5	852	1100
	121-40-2800-03K	123-40-2800-03K	2978	2625	112	2910	2691	56	33	2797.5	2802.5	100	12	8	M10×1	18	3078	168	2520	141	90	+0.5	960	1250
	122-40-2800-03K	124-40-2800-03K	2978	2625	112	2910	2691	56	33	2797.5	2802.5	100	12	8	M10×1	20	3080	151	2520	127	90	+0.5	960	1250
	121-50-3150-03K	123-50-3150-03K	3376	2922	134	3286	3014	56	45	3147.5	3152.5	122	12	8	M10×1	20	3480	171	2820	142	110	+0.5	1380	2150
	122-50-3150-03K	124-50-3150-03K	3376	2922	134	3286	3014	56	45	3147.5	3152.5	122	12	8	M10×1	22	3476	155	2816	129	110	+0.5	1380	2150
120-50-3550-03K	121-50-3550-03K	123-50-3550-03K	3776	3322	134	3686	3414	56	45	3547.5	3552.5	122	12	8	M10×1	20	3880	191	3220	162	110	+0.5	1570	2470
	122-50-3550-03K	124-50-3550-03K	3776	3322	134	3686	3414	56	45	3547.5	3552.5	122	12	8	M10×1	22	3894	174	3212	147	110	+0.5	1570	2470
	121-50-4000-03K	123-50-4000-03K	4226	3772	134	4136	3864	60	45	3997.5	4002.5	122	12	10	M10×1	22	4334	194	3652	167	110	+0.5	1760	2800
	122-50-4000-03K	124-50-4000-03K	4226	3772	134	4136	3864	60	45	3997.5	4002.5	122	12	10	M10×1	25	4350	171	3650	147	110	+0.5	1760	2800
	121-50-4500-03K	123-50-4500-03K	4726	4272	134	4636	4364	60	45	4497.5	4502.5	122	12	10	M10×1	22	3840	217	4158	190	110	+0.5	1980	3100
122-50-4500-03K	124-50-4500-03K	4726	4272	134	4636	4364	60	45	4497.5	4502.5	122	12	10	M10×1	25	4850	191	4150	167	110	+0.5	1980	3100	

TRIPLE-ROW CYLINDRICAL ROLLER BEARING SLEWING RINGS






轴承型号 Designations			外形尺寸 Boundary dimensions			安装孔尺寸 Bolt hole diameter			结 构 尺 寸 Structure dimensions						齿 轮 参 数 Gear parameters						额定负荷 Basic load ratings		质量 Mass		
无齿式	外齿式	内齿式	D	d	H	D1	D2	n	φ	D3	d1	h1	h2	n3	φ3	m	Da	Z	da	Z	b	x	Coa	Cor	kg
non-gear type	external gear type	internal gear type	mm			mm			mm	(D3')	(d1')				mm		mm		mm		mm		mm	10 ⁴ N	
130-25-500-**-	131-25-500-**-	133-25-500-**-	634	366	148	598	402	24	18	537	526	32	10	4×2	M10×1	5	665	130	335	68	80	+0.5	275	35.5	224
	132-25-500-**-	134-25-500-**-	634	366	148	598	402	24	18	474	463	32	10	4×2	M10×1	6	666	108	336	57	80	+0.5	275	35.5	224
130-25-560-**-	131-25-560-**-	133-25-560-**-	694	426	148	658	462	24	18	597	586	32	10	4×2	M10×1	5	725	142	395	80	80	+0.5	308	39.9	240
	132-25-560-**-	134-25-560-**-	694	426	148	658	462	24	18	534	523	32	10	4×2	M10×1	6	726	118	396	67	80	+0.5	308	39.9	240
130-25-630-**-	131-25-630-**-	133-25-630-**-	764	496	148	728	532	28	18	667	656	32	10	4×2	M10×1	6	810	132	456	77	80	+0.5	345	45.1	270
	132-25-630-**-	134-25-630-**-	764	496	148	728	532	28	18	(604)	(593)	32	10	4×2	M10×1	8	808	98	456	58	60	+0.5	345	45.1	270
130-25-710-**-	131-25-710-**-	133-25-710-**-	844	576	148	808	612	28	18	747	736	32	10	4×2	M10×1	6	888	145	534	90	80	+0.5	388	51.7	300
	132-25-710-**-	134-25-710-**-	844	576	148	808	612	28	18	(684)	(673)	32	10	4×2	M10×1	8	888	108	536	68	80	+0.5	388	51.7	300
130-32-800-**-	131-32-800-**-	133-32-800-**-	964	636	182	920	680	36	22	841	830	40	10	4×2	M10×1	8	1008	123	592	75	120	+0.5	549	71.2	500
	132-32-800-**-	134-32-800-**-	964	636	182	920	680	36	22	(770)	759	40	10	4×2	M10×1	10	1010	98	590	60	120	+0.5	549	71.2	500
130-32-900-**-	131-32-900-**-	133-32-900-**-	1064	736	182	1020	780	36	22	941	930	40	10	4×2	M10×1	8	1104	135	688	87	120	+0.5	619	80.8	600
	132-32-900-**-	134-32-900-**-	1064	736	182	1020	780	36	22	(870)	(859)	40	10	4×2	M10×1	10	1110	108	690	70	120	+0.5	619	80.8	600
130-32-1000-**-	131-32-1000-**-	133-32-1000-**-	1164	836	182	1120	880	40	22	1041	1030	40	10	5×2	M10×1	10	1220	119	780	79	120	+0.5	689	90.3	680
	132-32-1000-**-	134-32-1000-**-	1164	836	182	1120	880	40	22	(970)	(959)	40	10	5×2	M10×1	12	1224	99	780	66	120	+0.5	689	90.3	680
130-32-1120-**-	131-32-1120-**-	133-32-1120-**-	1284	956	182	1240	1000	40	22	1161	1150	40	10	5×2	M10×1	10	1340	131	900	91	120	+0.5	768	102	820
	132-32-1120-**-	134-32-1120-**-	1284	956	182	1240	1000	40	22	(1090)	(1079)	40	10	5×2	M10×1	12	1344	109	900	76	120	+0.5	768	102	820
130-40-1250-**-	131-40-1250-**-	133-40-1250-**-	1445	1055	220	1393	1107	45	26	1300	1290	50	10	5×2	M10×1	12	1512	123	984	83	150	+0.5	1110	146	1200
	132-40-1250-**-	134-40-1250-**-	1445	1055	220	1393	1107	45	26	(1210)	(1200)	50	10	5×2	M10×1	14	1512	105	980	71	150	+0.5	1110	146	1200

TRIPLE-ROW CYLINDRICAL ROLLER BEARING SLEWING RINGS



轴承型号 Designations			外形尺寸 Boundary dimensions			安装孔尺寸 Bolt hole diameter			结 构 尺 寸 Structure dimensions						齿 轮 参 数 Gear parameters				额定负荷 Basic load ratings		质量 Mass				
无齿式 non-gear type	外齿式 external gear type	内齿式 internal gear type	D mm	d mm	H mm	D1 mm	D2 mm	n mm	φ mm	D3 (D3')	d1 (d1')	h1	h2	n3	φ3 mm	m	Da mm	Z	da mm	Z	b mm	x	Coa 10 ⁴ N	Cor 10 ⁴ N	kg
130-40-1400-**-	131-40-1400-**-	133-40-1400-**-	1595	1205	220	1543	1257	45	26	1450	1440	50	10	5×2	M10×1	12	1668	136	1140	96	150	+0.5	1240	165	1300
	132-40-1400-**-	134-40-1400-**-	1595	1205	220	1543	1257	45	26	(1360)	(1350)	50	10	5×2	M10×1	14	1666	116	1134	80	150	+0.5	1240	165	1300
130-40-1600-**-	131-40-1600-**-	133-40-1600-**-	1795	1405	220	1743	1457	48	26	1650	1640	50	10	6×2	M10×1	14	1876	131	1330	96	150	+0.5	1420	190	1520
	132-40-1600-**-	134-40-1600-**-	1795	1405	220	1743	1457	48	26	(1560)	(1550)	50	10	6×2	M10×1	16	1872	114	1328	84	150	+0.5	1420	190	1520
130-40-1800-**-	131-40-1800-**-	133-40-1800-**-	1995	1605	220	1943	1657	48	26	1850	1840	50	10	6×2	M10×1	14	2072	145	1526	110	150	+0.5	1590	215	1750
	132-40-1800-**-	134-40-1800-**-	1995	1605	220	1943	1657	48	26	(1760)	(1750)	50	10	6×2	M10×1	16	2080	127	1520	96	150	+0.5	1590	215	1750
130-45-2000-**-	131-25-2000-03		2195	1816	150	2127	1885	60	33		2041	33	13	3×5	ZG1/4in	16	2267	138	--	--	105	+0.9	1690	66.3	1120
	131-45-2000-04		2221	1779	231	2155	1845	60	33	2059	2055	54	12	6×3	M10×1	16	2304	141	1696	107	160	+0.5	2050	239	2230
	131-45-2000-**-	133-45-2000-**-	2221	1779	231	2155	1845	60	33	2055	2033	54	12	6×2	M10×1	16	2304	141	1696	107	160	+0.5	2050	239	2400
	132-45-2000-**-	134-45-2000-**-	2221	1779	231	2155	1845	60	33	(1967)	(1945)	54	12	6×2	M10×1	18	2304	125	1692	95	160	+0.5	2050	239	2400
130-45-2240-**-	131-45-2240-**-	133-45-2240-**-	2461	2019	231	2395	2085	60	33	2295	2273	54	12	6×2	M10×1	16	2560	157	1920	121	160	+0.5	2310	268	2700
	132-45-2240-**-	134-45-2240-**-	2461	2019	231	2395	2085	60	33	(2207)	(2185)	54	12	6×2	M10×1	18	2556	139	1926	108	160	+0.5	2310	268	2700
130-45-2500-**-	131-45-2500-04		2721	2279	231	2655	2345	72	33	2555	2561	54	12	8×3	M10×1	18	2826	154	--	--	160	+0.5	2580	302	2834
	131-45-2500-**-	133-45-2500-**-	2721	2279	231	2655	2345	72	33	2555	2533	54	12	8×2	M10×1	18	2826	154	2178	122	160	+0.5	2580	302	3000
	132-45-2500-**-	134-45-2500-**-	2721	2279	231	2655	2345	72	33	(2467)	(2445)	54	12	8×2	M10×1	20	2820	138	2180	110	160	+0.5	2580	302	3000
130-45-2800-**-	131-45-2800-**-	133-45-2800-**-	3021	2579	231	2955	2645	72	33	2855	2833	54	12	8×2	M10×1	18	3114	170	2484	139	160	+0.5	2880	339	3400
	132-45-2800-**-	134-45-2800-**-	3021	2579	231	2955	2645	72	33	(2767)	(2745)	54	12	8×2	M10×1	20	3120	153	2480	125	160	+0.5	2880	339	3400
	132-45-2800-03		3021	2579	231	2955	2645	72	33	2855	2833	54	12	8×3	M10×1	20	3120	153			160	+0.5	2896	323	3031
	132-45-2800-12		3021	2579	231	2955	2645	72	33	2855	2833	54	12	8×3	M10×1	18	3114	170	--	--	160	+0.5	2896	323	3010
130-50-3150-**-	131-50-3150-**-	133-50-3150-**-	3432	2868	270	3342	2958	72	45	3213	3196	65	12	8X2	M10×1	20	3540	174	2760	139	180	0.5	3590	381	5000

TRIPLE-ROW CYLINDRICAL ROLLER BEARING SLEWING RINGS



轴承型号 Designations			外形尺寸 Boundary dimensions			安装孔尺寸 Bolt hole diameter				结 构 尺 寸 Structure dimensions						齿 轮 参 数 Gear parameters						额定负荷 Basic load ratings		质量 Mass			
无齿式	外齿式	内齿式	D	d	H	D1	D2	n	φ	D3	d1	h1	h2	n3	φ3	m	Da	Z	da	Z	b	x	Coa	Cor	kg		
non-gear type	external gear type	internal gear type	mm			mm			mm	(D3')	(d1')		mm		mm		mm		mm		mm		10 ⁴ N				
130-50-3150-**	132-50-3150-12K	134-50-3150-11K	3432	2868	270	3342	2958	72	45	(3104)	(3087)	65	12	8×2	M10×1	22	3542	158	2750	126	180	+0.5	3590	381	5000		
130-50-3150-12K			3432	2868	270	3342	2958	72	45	3103	3086	50	12	8×2	M10×1									3735	502	4900	
			131-30-3150-12K	3376	2922	182	3286	3014	56	45	3190	3180	40	10	8×3	M10×1	20	3476	171			120	+0.5	2050	202	2308	
			131-50-3150-12K	3432	2868	270	3342	2958	72	45	3214	3197	50	12	8×2	ZG1/4in	20	3540	174			180	+0.5	3735	474	5404	
			132-50-3150-12K	3432	2868	270	3342	2958	72	45	3214	3197	50	12	8×2	ZG1/4in	22	3542	158			180	+0.5	3735	474	5409	
			132-50-3150-12K1	3432	2868	270	3342	2958	72	45	3214	3197	50	12	8×3	M10×1	20	3536	174			195	+0.5	3735	474	5385	
				133-50-3150-11K	3432	2868	270	3342	2958	60	39	3103	3086	50	12	8×2	M10×1	20			2761	139	180	+0.5	3575	501	5174
				133-50-3150-12K	3432	2868	270	3342	2958	60	39	3103	3086	50	12	8×2	M10×1	20			2761	139	180	+0.5	3575	501	5174
				133-50-3150-12K1	3432	2868	270	3342	2958	60	39	3103	3086	50	12	8×2	M10×1	18			2754	154	180	+0.5	3575	501	5174
				134-50-3150-11K	3432	2868	270	3342	2958	72	45	3103	3086	50	12	6×2	ZG1/4in	22			2759	126	180	+0.5	3575	501	5104
130-50-3550-**	131-50-3550-**	133-50-3550-**	3832	3268	270	3742	3358	72	45	3613	3596	65	12	8×2	M10×1	20	3940	194	3160	159	180	+0.5	4040	431	5600		
	132-50-3550-**	134-50-3550-**	3832	3268	270	3742	3358	72	45	(3504)	(3487)	65	12	8×2	M10×1	22	3938	176	3146	144	180	+0.5	4040	431	5600		
	132-50-3550-03K		3832	3268	270	3742	3358	72	45	3613	3596	65	12	8×3	M10×1	22	3934	176			180	+0.5	4105	401	4960		
	132-50-3550-12		3832	3268	270	3742	3358	72	45	3613	3596	65	12	8×3	M10×1	22	3938	176			180	+0.5	4105	401	5318		
130-50-4000-**	131-50-4000-**	133-50-4000-**	4282	3718	270	4192	3808	80	45	4063	4046	65	12	8×2	M10×1	22	4400	197	3608	165	180	+0.5	4560	487	6400		
	132-50-4000-**	134-50-4000-**	4282	3718	270	4192	3808	80	45	3954	3937	65	12	8×2	M10×1	25	4400	173	3600	145	180	+0.5	4560	487	6400		
	131-50-4000-04K		4282	3718	270	4192	3808	80	45	4063	4046	65	12	8×2	M10×1	22	4400	197			180	+0.5	4502	450	6377		
	132-50-4000-12		4282	3718	270	4192	3908	80	45	4063	4046	65	12	8×3	M10×1	25	4400	173			180	+0.5	4502	450	6377		
130-50-4500-40	131-50-4500-**	133-50-4500-**	4782	4218	270	4692	4308	80	45	4563	4546	65	12	8×2	M10×1	22	4906	220	4114	188	185	+0.5	5445	580	6942		
	132-50-4500-**	134-50-4500-**	4782	4218	270	4692	4308	80	45	(4454)	(4437)	65	12	8×2	M10×1	25	4906	193	4100	165	185	+0.5	5445	580			
	131-50-4500-04		4782	4218	270	4692	4308	80	45	4565	4546	60	12	8×3	M10×1	20	4880	242			185	+0.5	4900	507	7250		
	132-50-4500-04		4782	4218	270	4692	4308	80	45	4565	4546	60	12	10×2	M14×1.5	25	4895	193			185	+0.5	4900	506	7333		
	131-60-5000-04		5320	4670	320	5220	4766	100	45	5082	5062	65	18	10×3	M10×1	20	5440	270			220	+0.5	6834	955	11752		

FORTE Slewing Bearings

FORTE 上海孚特意机械有限公司
SHANGHAI FORTE MACHINERY CO., LTD.



上海孚特意机械有限公司
Shanghai Forte Machinery Co., LTD.

电话/Tel: +86 (0)21 67751461

电话/Tel: +86 (0)21 37826205

传真/Fax: +86 (0)21 67751462

邮箱/Email: service@forte-cn.com

地址: 中国上海市松江区文诚路500弄6号611室(201620)

Add: Room 611, No. 6, Lane 500, Wencheng Road, Songjiang District, Shanghai, China

